



GM TIS 2 WEB Subscription Guide

NOTE: This guide shows the steps required to purchase the on-line GM TIS2Web Application. The process shown is subject to change at any time.



- Go to: www.acdelcotds.com/acdelco/action/subscribehome
- Click on “Subscribe Now”.



- Click on “click here”.


GM TIS 2 WEB Subscription Guide

The screenshot shows the ACDelco TechConnect registration page. The form includes the following fields and instructions:


- First Name***, **Middle Name**, **Last Name***: Text input fields.
- Social Security Number**: Text input field with instruction: "Last 4 digits of SSN".
- Email***, **Confirm Email***: Text input fields with instruction: "Very important, please double check".
- Login Name***: Text input field with instruction: "minimum 8 characters and maximum 12 characters. First 6 characters should not be numeric. No Spaces.".
- Password***, **Confirm Password***: Text input fields with instruction: "Between 6 and 20 characters long, numerals and letters only".
- Address 1***, **Address 2**: Text input fields.
- City***, **State*** (dropdown), **Country*** (dropdown): Address fields.
- Zip***: Text input field with instruction: "99999 or 99999-9999".
- Home Phone**: Text input field with instruction: "12-345-678-9012".
- Secret Question***: Dropdown menu with "What city were you born?".
- Secret Answer***: Text input field.
- Required Field***: Section containing "Submit" and "Cancel/Clear" buttons.

- Note: “Login Name” and “Password” is case-sensitive. Please make note of your information.
- Fill in information as required and click on “Submit”.

GM TIS 2 WEB Subscription Guide




- An email will be sent to the email address specified. Click “[here](#)” to go back to the Login Page to log in and log in as requested.




- Scroll to bottom of Terms and Conditions of Use, if agreeable, select “Accept” and then “Continue”.

GM TIS 2 WEB Subscription Guide




- Click on “Service Information”.




- Click on the “Subscribe Now” shown. The one shown is for the reprogramming data for J2534 devices.

GM TIS 2 WEB Subscription Guide



- Click on “1 Year (\$995)” and “Retype Email” and select “Continue”.



- Fill out Credit Card information and click on “Continue”.
- The next screen will indicate your registration success and an email will be sent for confirmation.



GM TIS 2 WEB Subscription Guide


BLANK PAGE




Orig. Date: 12/12/99	Rev. Date: 6/11/10	Rev. Level: 001	Doc. # B1
----------------------	--------------------	-----------------	-----------

GM TIS2Web Initial Set-up Guide


NOTE: This process should only need to be performed the first time using TIS2Web on a PC. First ensure the PC meets the minimum requirements and that pop-up blockers, etc., are disabled. Go through the FLASH2 Console application and sign-on to the ACDelco account. Follow the following screens once the first screen shown is reached.




- Click on “Start SPS”. The next screen will open in a separate, new window.




- Click on “Settings”. The next screen will open in a separate, new window.



- Click on the “Diagnostic” tab. Make sure “J2534 FLASH2 All-Makes Reprogrammer” is displayed in the “Device” area and then “Test Connection”.



- You should see “M4384 : Test was successful”. If not, close out everything and try again. If this second attempt does not resolve the issue, there is something that is occupying one of the Com ports on the PC. A couple things that may be occupying a Com port like a modem or “sync” software, such as: HotSync®. These must be completely removed/uninstalled and then try again. You must get the “Test was successful” message.




- Next, click on the “Common” tab, select “North American Operations” and click “Ok”.

GM TIS2Web On/Off-Car Reprogramming Guide


NOTE: This guide is and shows the common steps in reprogramming. Application-specific variations may not be represented. Simply follow the applicable screen prompts and proceed as indicated. This process is subject to change w/o notice.



- Click on the GM icon.




- Click on "FLASH2 Reprogramming".



- Click either "On-Car" or "Off-Car" as applicable.




- Read “Warning” information and click on “Next”.



- On-Car only: It is strongly recommended that a “Battery Test” be conducted. Read the notes and click on “Battery Test”.




- On-Car only: Ensure Battery Test is within acceptable parameters. Click “Next”.




- Please read the “Important!” instructions and click “Next”.




- On-Car: make sure the vehicle’s Ignition Switch is in the “On” position and click “Ok”.
- Off-Car: make sure the FLASH2 tool’s Ignition Switch is in the “On” position and click “Ok”.



- Make the appropriate selection and click “Next”.




- Click “Use WebLink” and click “Next”. Please wait as your Internet Browser opens.



- Type in “User Name” and “Password” and click “Log In”.




- Scroll down to bottom and click on “Accept”, if you agree, and “Continue”.




- Click on “Service Information”.


GM TIS2Web On/Off-Car Reprogramming Guide




- Click “TIS2Web – Service Programming”.




- Click on “Service Programming System (SPS)” icon.



- Click on “Start SPS”. (Note: any delay corresponds to Internet provider connection speed and user volume.) The next screen will open a separate, new window.



- Always Click on SKIP




- Click on “J2534 FLASH2 All-Makes Reprogrammer” and “Replace and Program ECU” and click “Next”. (Note: “Replace ECU” option will only allow reprogramming if a new calibration is available. “Replace and Reprogram ECU” will allow programming over the same, current calibration.)


GM TIS2Web On/Off-Car Reprogramming Guide



- Click "Next".




- Using the dropdown arrows, select "Salesmake, Model Year, Vehicle Type, Car Line, etc.", until all required selections are complete. Click "Next".



- Input the correct VIN for the vehicle the ECU is being used on and click "Next".


GM TIS2Web On/Off-Car Reprogramming Guide




- Select “PCM/VCM” and “Normal” and click “Next”. (If other modules are being programmed, the remaining few screens may be different. Simply read and follow on-screen instructions as requested and respond accordingly.)




- Note any “Controller Specific Instructions”, if any.
- On-Car: Follow on-screen directions as applicable and click “Next”.
- Off-Car: Click “Next”.




- Refer to Current Calibration and Index shown. Make appropriate Calibration selections where required.



- Summary of calibration selections made. Click “Next”...



- Reprogramming screen....




- Programming Complete. Note any “Controller Specific Instructions”, if any.
- Click “Cancel” to close the program.

NOTE: If NEW is selected be certain to allow at least 30 with “ignition” off. Failure to allow 30 seconds before disconnecting the Console may result in a lost or corrupt VIN to be stored in ECM memory.



- Close GM TIS 2 WEB application by clicking on the “open door”.



- Click “Logout”.




- Close “Internet Explorer” by clicking on the red “x” as shown.



- Read and click “Next”.


NOTE: Failure to allow 30 seconds before disconnecting the Console may result in a lost or corrupt VIN to be stored in ECM memory.




- Read and click “Ok”.



- On-Car: make sure the vehicle’s Ignition Switch is in the “Off” position and click “OK”.
- Off-Car: make sure the FLASH2 tool’s Ignition Switch is in the “Off” position and click “Ok”.



- You must wait 30 seconds after successfully reprogramming an ECU to ensure the flash devices have time to complete their write cycle before power is removed. If the event was not successful, you may use the “Skip” button. Otherwise, wait the 30 seconds.



- You may click on “Get Status”, make sure the proper “Ignition Switch” is turned on and the information for the reprogramming event will appear. You may also Print this information. Click “Finish” when done. **Note:** Information that may not appear or appear correctly means that the module/vehicle simply doesn’t support the data.

End of Flash process.